



Copper Edge Metals Specifications

MATERIALS

A. All ACM copper edge metal products shall be made of a Standard sheet copper: cold rolled ounce weight (10-ounce and 16-ounce) copper sheet complying with ASTM B370. Unless otherwise noted, temper shall be H00.

<u>B. Thickness</u>	<u>Products</u>
10 oz.	Select Drip Edge, Flat Shingles, Step Flashings, Roll Valley, & W-Valley
16 oz.	Select Drip Edge, Flat Shingles, Step Flashings, Roll Valley, W-Valley, & Flat Sheets

APPLICATIONS

ACM Copper edge metal products are designed for residential and light commercial applications. Copper edge metal products shall be attached per contractor's direction.

CONSIDERATIONS

Corrosion is likely to happen with direct contact of aluminum products to certain dissimilar materials or water run-off from same such materials. Care should be taken to avoid contact of aluminum with any corrosive materials during the installation process, including, but not limited to: concrete, stucco, pretreated lumber, corrosive chemicals, fiber cement products, masonry cement, roofing made with metallic granules of dissimilar metals (aluminum, zinc, steel, etc.), salt, and dissimilar metals.

*Some products may be available in specific geographic distribution areas.

ACM – Beloit
1600 Park Avenue
Beloit, WI 53511
Ph: 877.279.5096
Fax: 608.365.0493

ACM – Shawnee
4124 Powell Drive
Shawnee, KS 66226
Ph: 877.279.5096
Fax: 608.365.0493

ACM – Apollo Beach
6938 N. Hwy 41
Apollo Beach, FL 33572
Ph: 800.749.4067
Fax: 608.364.0598

ACM – Houston
11615 Brittmoore Park Dr.
Houston, TX 77041
Ph: 800.357.7523
Fax: 713.466.5404

ACM – Lodi
1307 E. Pine Street
Lodi, CA 95240
Ph: 877.213.5962
Fax: 608.362.0599