



# Copper Rainware Specifications

## MATERIALS

A. All ACM copper rainware products shall be made of a Standard sheet copper: cold-rolled ounce weight (10-ounce and 16-ounce copper sheet complying with ASTM B370. Unless otherwise noted, temper shall be H00.

<u>B. Thickness</u>	<u>Products</u>
10 oz.	Downspouts & Elbows: 2 x 3, 3 x 4, 3", & 4" Rounds, End Caps: 5" & 6" K-style, 6" Half Rounds
16 oz.	Gutter Coil: 11 7/8" & 15", Outlets, Miters, Downspout Bands & Clips, 6" Half-Round Gutter 10' and 20' lengths

## APPLICATIONS

ACM Copper rainware is designed for residential and light commercial applications. Copper rainware shall be attached per contractor's direction and state and local building codes.

## CONSIDERATIONS

Corrosion is likely to happen with direct contact of aluminum products to certain dissimilar materials or water run-off from same such materials. Care should be taken to avoid contact of aluminum with any corrosive materials during the installation process, including, but not limited to: concrete, stucco, pretreated lumber, corrosive chemicals, fiber cement products, masonry cement, roofing made with metallic granules of dissimilar metals (aluminum, zinc, steel, etc.), salt, and dissimilar metals.

\*Some products may be available in specific geographic distribution areas.

ACM – Beloit  
1600 Park Avenue  
Beloit, WI 53511  
Ph: 877.279.5096  
Fax: 608.365.0493

ACM – Shawnee  
4124 Powell Drive  
Shawnee, KS 66226  
Ph: 877.279.5096  
Fax: 608.365.0493

ACM – Apollo Beach  
6938 N. Hwy 41  
Apollo Beach, FL 33572  
Ph: 800.749.4067  
Fax: 608.364.0598

ACM – Houston  
11615 Brittmoore Park Dr.  
Houston, TX 77041  
Ph: 800.357.7523  
Fax: 713.466.5404

ACM – Lodi  
1307 E. Pine Street  
Lodi, CA 95240  
Ph: 877.213.5962  
Fax: 608.362.0599