



# Galvalume® Downspout & Elbow Specifications

## MATERIALS

- A. GALVALUME® coatings are approximately 43% zinc, 55% aluminum, with the balance containing primarily silicon and iron for good coating adhesion.
- B. ACM GALVALUME® 26 gauge mill finish downspouts and elbows are available in 2x3, 3x4, 3” & 4” round sizes.

## APPLICATIONS

ACM GALVALUME® downspouts and elbows are designed for residential and light commercial applications. GALVALUME® downspouts and elbows shall be attached per contractor’s direction and state and local building codes.

## CONSIDERATIONS

Corrosion is likely to happen with direct contact of GALVALUME® product(s) to certain dissimilar materials or water run-off from these materials. Care should be taken to avoid contact of GALVALUME® product(s) with any corrosive materials during the installation process, including, but not limited to: concrete, stucco, pretreated lumber, corrosive chemicals, fiber cement products, masonry cement, roofing made with metallic granules of dissimilar metals (copper, zinc, aluminum, etc.), salt, and dissimilar metals.

- \* Some products may be limited to specific geographic distribution areas.

ACM – Beloit  
1600 Park Avenue  
Beloit, WI 53511  
Ph: 877.279.5096  
Fax: 608.365.0493

ACM – Shawnee  
4124 Powell Drive  
Shawnee, KS 66226  
Ph: 877.279.5096  
Fax: 608.365.0493

ACM – Apollo Beach  
6938 N. Hwy 41  
Apollo Beach, FL 33572  
Ph: 800.749.4067  
Fax: 608.364.0598

ACM – Houston  
11615 Brittmoore Park Dr.  
Houston, TX 77041  
Ph: 800.357.7523  
Fax: 713.466.5404

ACM – Lodi  
1307 E. Pine Street  
Lodi, CA 95240  
Ph: 877.213.5962  
Fax: 608.362.0599